



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: RBC53

UPS Replacement Battery Cartridge Kit for select Tripp Lite, Best, Powerware, Liebert and other UPS

Highlights



- Up to 30% longer runtime than basic replacements
- OEM certified premium batteries
- Rugged, leakproof construction
- Maintenance-free
- Wide operating temperature range

Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original manufacturer specifications and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. Compatible with a wide variety UPS brands and models. See Tripp Lite's UPS replacement battery web page to confirm compatibility and quantity required. Includes 18 month warranty.

Applications

- Extends the operating life of older UPS systems
- Restores or enhances runtimes of all UPS systems exhibiting reduced power failure runtime

Package Includes

- 3 12V UPS replacement batteries
- Instruction manual with installation, recycling and warranty information

Features

- Restore UPS runtime performance to its original runtime specifications
- Reusable packaging contains expired batteries for recycling center delivery
- Compatible with a variety of UPS brands
- Includes 18 month warranty

Specifications

BATTERY	
Typical battery lifespan	3 - 5 years, depending on host UPS operating conditions
Included Battery Set	Includes 3 12V batteries
PHYSICAL	
Shipping weight (lbs)	19 (Package includes 3 batteries)
Shipping weight (kg)	8.6 (Package includes 3 batteries)

Shipping Dimensions (HWD/in)	6 x 7.5 x 12
Shipping Dimensions (HWD/cm)	15.2 x 19.1 x 30.5
Unit Dimensions (HWD/in)	Each battery measures 3.6875 x 2.5 x 5.875
Unit Dimensions (HWD/cm)	Each battery measures 9.4 x 6.4 x 14.9
ENVIRONMENTAL	
Relative Humidity	0 - 95% non-condensing
Operating Elevation (ft)	0 - 10,000
Storage Elevation (ft)	0 - 50,000
WARRANTY	
Product Warranty Period	18 months

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2544.